



4046 Extension ladder, two-section

- > Inner width of the ladder 300 mm (upper section).
- > Stiles of seamless extruded profiles with ergonomic shape.
- › Rolled profile rungs.
- Ladder feet pressed into the stile.
- Guide fittings made of solid steel.







Number of rungs		2×10	2×12	2×14	2×16
Stile	approx. mm	66	71	83	83
Number of rungs at max. extension		17	21	25	29
Length retracted	approx. m	2.90	3.46	4.02	4.58
Length extended	approx. m	4.86	5.98	7.10	8.22
Standing height	approx. m	3.74	4.82	5.90	6.98
Working height	approx. m	5.24	6.32	7.40	8.48
Reach height	approx. m	5.74	6.82	7.90	8.98
Width extended top/bottom	approx. mm	355/425	355/425	355/425	355/425
Weight	approx. kg	10.2	14.0	16.5	20.6
EAN-Code		4019502339132	4019502339149	4019502339156	4019502339163
Order no.		404620	404624	404628	404632

For an explanation of working/standing/reach height see on page 5.

Recommended accessories:



Cross-beam for ladder section



Set of foot pikes for stiles



Telescopic wall spacer Ladder holder set



for rung ladders for gutters



Ladder bracket set for roof racks