



Note:
Hinges must be kept clean and regularly lubricated.

4042 Telescopic ladder

- › Can be used as length adjustable leaning ladder, freestanding ladder and stairway ladder.
- › Stable adaptation to uneven floor surfaces or stairs possible.
- › Rungs on inner ladder part made of rolled sections. Rungs on outer ladder part made of heavily shaped extruded profile.
- › Low space requirements for storage and transport.
- › Plastic-coated steel handles for the locking devices.
- › Steel hinge with locking clamp easy to use.
- › In the rung ladder position, the hinge must be released by hand before the ladder is folded together.



Number of rungs		4×4	4×5	4×6
Stile	approx. mm	60	60	60
Number of rungs	at max. extension	14	18	22
Length	leaning ladder approx. m	2.35 – 4.02	2.90 – 5.14	3.46 – 6.26
Standing height	step ladder approx. m	1.26	1.80	2.35
Working height	step ladder approx. m	2.76	3.30	3.85
Reach height	step ladder approx. m	3.26	3.80	4.35
Standing height	leaning ladder approx. m	3.00	4.10	5.20
Working height	leaning ladder approx. m	4.50	5.60	6.70
Reach height	leaning ladder approx. m	5.00	6.10	7.20
Vertical height	step ladder approx. m	1.15 – 1.95	1.40 – 2.49	1.70 – 3.03
Width	as step ladder top/bottom approx. mm	355/560	355/630	355/700
Folded	L×W×H approx. m	1.20×0.55×0.20	1.50×0.65×0.20	1.80×0.70×0.20
Base width	retracted/extended approx. m	0.87/1.36	1.03/1.72	1.20/2.01
Weight	approx. kg	12.2	15.2	18.0
EAN-Code		4019502339385	4019502339392	4019502339408
Order no.		404216	404220	404224

For an explanation of working/standing/reach height see on page 5.

Recommended accessories:



P. 176

Folding universal ladder step



P. 182

Bucket hook for rung ladders



P. 182

Tool bag for aluminium ladders



P. 175

Foot extension for telescopic ladders



P. 174

Set of swivelling foot pikes for telescopic ladders



P. 180

Fixed castor set for telescopic ladders

Spare part:

- › Spare parts set rung covers, order no. 0054047, see on page 186.