



8080 Platform ladder with handrail

- › Step depth 80 mm.
- › Platform dimensions: 440 mm wide, 400 mm long.
- › Guardrail height above platform 800 mm.
- › On request, self-locking spring-loaded castors can be mounted on the ladder section/support section.
- › Large 450 mm tray for tools and small parts and suspension hook for buckets and small appliances.
- › Rigid safety bars fitted as standard ensure high stability.
- › Stable stiffening braces on first step.
- › With restraining straps from size 8.
- › The handrail is delivered unassembled but prepared for self assembly.



Number of steps incl. platform		4	5	6	7	8	9	10	12
Stile	approx. mm	71	71	71	71	71	71	71	71
Length	approx. m	1.95	2.20	2.45	2.70	2.95	3.20	3.45	3.95
Standing height (height to platform)	approx. m	0.95	1.15	1.40	1.65	1.85	2.10	2.35	2.80
Working height	approx. m	2.45	2.65	2.90	3.15	3.35	3.60	3.85	4.30
Reach height	approx. m	2.95	3.15	3.40	3.65	3.85	4.10	4.35	4.80
Total vertical height	approx. m	1.75	2.00	2.20	2.55	2.70	3.00	3.15	3.60
Width	approx. mm	650	670	700	730	750	780	800	850
Base width	approx. m	1.00	1.15	1.30	1.60	1.75	1.90	2.05	2.35
Weight	approx. kg	9.7	10.7	12.0	13.3	14.4	16.0	17.2	22.2
EAN-Code		4019502316171	4019502316188	4019502316195	4019502353732	4019502316201	4019502353749	4019502316218	4019502316225
Order no.		808004	808005	808006	808007	808008	808009	808010	808012

For an explanation of working/standing/reach height see on page 5.

Recommended accessories:

- › **4 spring-loaded castors assembled at HYMER**
Swivelling/fixed castors, freely selectable according to variant.
(Please specify the desired mounting variant for the spring-loaded castors in your order.)
With the variant of swivelling castors fixed to the ladder section*, one castor with locking brake is included.
It is recommended to fit spring-loaded castors depending on the sense of safety of the user but only up to size 6.
- › For greater heights we recommend the use of tip and roll wheels, see on page 179.
- › Sets of spring-loaded castors for self assembly, see on page 179.

	Variant 1	Variant 2	Variant 3	Variant 4
Ladder section	2 swivelling castors*	2 swivelling castors*	2 fixed castors	2 fixed castors
Support section	2 fixed castors	2 swivelling castors	2 fixed castors	2 swivelling castors



Swivelling castor without locking brake



Swivelling castor with locking brake



Fixed castor