

STANDARD FIBREGLASS LADDERS

FIBREGLASS SINGLE SECTION LADDER

Standard
UNE-EN 131Standard
UNE-EN 50528Insulation
100 KV

Ref.	N° Rungs			Kg
F6105	5	1485	400	5
F6106	6	1765	400	5.5
F6107	7	2045	400	6
F6108	8	2325	400	6.5
F6109	9	2650	400	7
F6110	10	2990	400	8.5
F6111	11	3270	400	9.5
F6112	12	3550	400	10.5
F6113	13	3830	400	11
F6114	14	4110	400	12
F7115	15	4390	400	13
F7116	16	4670	400	14
F7117	17	4950	400	15
F7118	18	5230	400	16
F7119	19	5510	400	17
F7120	20	5790	400	18
F7121	21	6070	400	19

* See optional accessories available on page 26-29.

Ref. F6114



Equipped with swivel feet from ref. F6110 upwards



Optional height-adjustable legs



Optional base stabiliser. According to new standard UNE-EN 131 when height exceeds 3 m.

FIBREGLASS SINGLE SECTION FOLDING LADDER

Equipped with a locking system that allows its use as a double-sided ladder or as a single section ladder and permits to fold it for transport and storage.

Standard
UNE-EN 131Standard
UNE-EN 50528Insulation
100 KV

Ref.	N° Rungs			Kg
F6106P	2x3	894	1726	6
F6108P	2x4	1180	2280	8
F6110P	2x5	1460	2840	9
F6112P	2x6	1740	3400	11

Ref. F6110P

